



## TECHNICAL SHEET

### AIR-OPERATED GREASE PUMPS R=100:1

#### Features:

**Ref.45031032.**

Air-operated Grease pump R=100:1 for standard drums of 20-30 kg.  
 Air inlet connection: F 1/4”G.  
 Grease Delivery capacity 6 bar: 1000 gr/min.  
 Shank diameter: 30mm.  
 Shank length: 480mm.

**Ref.45031034.**

Air-operated Grease pump R=100:1 for standard drums of 50-60 kg  
 Air inlet connection: F 1/4”G.  
 Grease Delivery capacity 6 bar: 1000 gr/min.  
 Shank diameter: 30mm.  
 Shank length: 750mm.



45031032    45031034    45031035

**Ref.45031035.**

Air-operated Grease pump R=100:1 for standard drums of 180-220 kg  
 Air inlet connection: F 1/4”G.  
 Grease Delivery capacity 6 bar: 1000 gr/min.  
 Shank diameter: 30mm.  
 Shank length: 950mm.

Reference	Description
45031032	Air-operated Grease pump R-100:1 for standard drums of 20-30Kg. Shank length 480mm
45031034	Air-operated Grease pump R-100:1 for standard drums of 50-60Kg. Shank length 750mm
45031035	Air-operated Grease pump R-100:1 for standard drums of 180-220Kg. Shank length 950mm